

1N5817W-1N5819W SCHOTTKY BARRIER DIODE


Features:

- Metal silicon junction, majority carrier conduction
- Guarding for overvoltage protection
- Low power loss, high efficiency
- High current capability
- Low forward voltage drop
- High surge capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

Mechanical Data:

- Case: SOD-123FL molded plastic body
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end
- Mounting Position: Any

Mechanical Dimensions: In mm/Inches



Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	3.55	3.85	0.140	0.152
B	2.60	2.90	0.102	0.114
C	1.75	1.95	0.069	0.077
D	0.90	1.40	0.035	0.055
E	0.70	1.20	0.028	0.047
G	0.25	-	0.010	-

SOD-123FL



Ordering Information:

Device	Package	Shipping
1N5817W-1N5819W	SOD-123FL(Pb-Free)	3000pcs / reel

For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification.

Maximum Ratings and Electrical Characteristics @T_A=25°C unless otherwise specified

Parameter Marking code	Symbol	1N5817W 12A	1N5818W 13A	1N5819W 14A	Unit
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	V
Maximum DC blocking voltage	V _R				
Maximum RMS voltage	V _{R(RMS)}	14	21	28	V
Maximum average forward rectified current 0.375" (9.5mm) lead length at T _A =90°C	I _{F(AV)}	1.0			A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	25.0			A
Maximum instantaneous forward voltage at 1.0A	V _F	0.45	0.55	0.60	V
Maximum DC reverse current T _A =25°C At rated DC blocking voltage T _A =100°C	I _R	0.5 10.0			mA
Typical junction capacitance (Note 1)	C _J	110			pF
Typical thermal resistance (Note 2)	R _{θJA}	115			°C/W
Operating junction and storage temperature range	T _J , T _{STG}	-55 to +125			°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. Mounted on 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas


AVERAGE FORWARD RECTIFIED CURRENT,
AMPERES


Fig.1-FORWARD CURRENT DERATING CURVE


PEAK FORWARD SURGE CURRENT,
AMPERES


Fig.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT


INSTANTANEOUS FORWARD
CURRENT, AMPERES


Fig.3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS


INSTANTANEOUS REVERSE CURRENT,
MICROAMPERES


Fig.4- TYPICAL REVERSE CHARACTERISTICS



1N5817W-1N5819W

Technical Data
Data Sheet N1756, Rev. -

Green Products

DISCLAIMER:

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC - Sangdest Microelectronics (Nanjing) Co., Ltd sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall SMC - Sangdest Microelectronics (Nanjing) Co., Ltd be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC - Sangdest Microelectronics (Nanjing) Co., Ltd assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall SMC - Sangdest Microelectronics (Nanjing) Co., Ltd be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC - Sangdest Microelectronics (Nanjing) Co., Ltd.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC - Sangdest Microelectronics (Nanjing) Co., Ltd.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..